

Tractor mounted sprayers by PTO via shaft developed to meet the different requirements of plant protection treatments. Sprayers extremely versatile and suitable, according to the applications, to operate in open-field cultivations, sprayer and distribute herbicides among the plant rows the availability of several mechanical and hydraulic spraying booms together with different equipments and option allow our sprayers to suit the requirement of the single users in the specific treatments.

Easily mountable on 3-pt of tractors

Level indicator on the tank

Polythene tanks

Easily cleanable water filter

Booms are removable for loading and transportation

High efficiency

Clean water tank

Pressure regulation



TECNICAL SPECIFICATIONS

Units	MHA 600	MHA 600	MHA 800	MHA 800	MHA 1000	MHA 1000
Pump Model (l/min)	C96	C96	C96	C96	C96	C96
Control Panel	VDR 50	VDR 50	VDR 50	VDR 50	VDR 50	VDR 50
Boom Length (m)	12	14	14	16	14	16
Noozle Type	Brass-Plastic	Brass-Plastic	Brass-Plastic	Brass-Plastic	Brass-Plastic	Brass-Plastic
Noozle Piece	24	28	28	32	28	32
Width (cm)	77	77	80	80	80	80
Lenght (cm)	140	140	158	158	165	165
Height (cm)	185	185	186	185	188	188
Bum Height (CM)	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Required Power (BG)	50	50	50	50	50	50
Working Transfer	540	540	540	540	540	540
Weight (kg)	385	405	422	485	450	515