

Turbo sprayers are used for vineyards, orchards and gardens. 400 and 600 lt. models are tractor mounted on 3-pt hitch by PTO. Strengthened Fibreglas or Polyethylene depot options. Pump are operated by power takeoff from tractor conveys pressuring chemical liquid to nozzles on fan. Fan is also operated with power take off and it sends pressured air out. Pressured chemical liquid is sprayed by adjustable nozzles around the fan by air circulation and any kind of tree can be disinfected. Fans are operated by two speed transmission. With separator on the fan, the rotation of the impeller can be prevented. By setting the angle and direction or by changing the plaque the nozzle on the fan, spraying distance and amount can be adjusted. By setting the direction of the propeller fan, the air flow can be controlled. Using distributor valve on the regulator right, left or spraying is done in both directions. Turbo fan delivers an average shot distance.

- Easily cleanable water filter
- Easily adjustable and usage
- High efficiency
- Pressure regulation
- Level indicator on the tank
- Clean water tank



TECNICAL SPECIFICATIONS

Units	MA 200	MA 400	MA 600	MA 800
Pump Model (l/min)	C71	C71	C96	C96
Control Panel	Latch	Latch	Latch	Latch
Noozle Type	Brass	Brass	Brass	Brass
Noozle Piece	4+4	5+5	5+5	5+5
Width (cm)	113	113	132	149
Lenght (cm)	163	163	164	164
Height (cm)	142	142	150	157
Cool Diameter (cm)	60	60	60	60
Work Width(cm)	8	8	8	8
Required Power (BG)	50	50	50	50
Working Transfer (d/d)	540	540	540	540
Air Flow (m ³ /h)	54000	54000	54000	54000
Weight (kg)	258	258	270	280