

It eases transport and operation in the divided field. During the operation in field, passing from mounting mode to movement mode is as simple as placing and removing the pin. Operation Fields: it provides an ease for breaking stubbles into pieces, preparing seed casing, scratching organic materials on the earth and challenging with excessively grown green grass especially in the climates with heavy rain. Used for scrapping pieces on the soil and stems of sunflower, wheat, rice, etc. It is easy to transport the machine from one field to another by assistance of hydraulic lifted wheels on the equipment. On the field, corner turnings become faster by the assistance of the hydraulic lifts operated the field, corner turnings become faster from tractor cabin. It is easy to adjust the working depth by the up and down movement of the wheels



TECNICAL SPECIFICATIONS

Units		CGD16	CGD18	CGD20	CGD22	CGD24	CGD26	CGD28	CGD30	CGD32	CGD34	CGD36
Number of Discs	pcs	16	18	20	22	24	26	28	30	32	34	36
Disc Diameter	mm	560x4,5										
Distance Between Disc	cm	22										
Bed Numbers on Crank	pcs	4	6	8	8	12						
Working Width	cm	176	198	220	242	264	286	308	330	352	374	396
Total Width	cm	200	222	244	266	288	310	332	354	376	398	420
Total Length	cm	520	527	562								
Total Height	cm	125										
Chassis	mm	100x100x6	100x150x6				100x200x6	100x200x8				
Weight	kg	1385	1485	1560	1660	1785	1860	1930	2010	2130	2280	2420
Tractor Power	hp	60-65	70-75	75-80	85-90	90-100	110-120	120-130	130-140	140-150	150-160	160-170