

Trailer is one of the equipments that must be included each agricultural establishments and farmers. It is commonly used for the transport of goods and materials in farm, field and gardens. Our modern trailers are intended for transport of various materials, in particular agricultural produce where precise tightness is required. Our innovative trailers are marked by: well-equipped standard versions, high loading capacity of box-bodies, long life using period. Some standard features like light system, tool box, chock, water tank, color option are available.



## TECNICAL SPECIFICATIONS

Units	Models				
Capacity	ton	1	3	4	5
Axle Type	-	Single	Single	Single	Single
Tipping Type	-	rear	rear	rear	rear
Length	cm	230	300	330	350
Width	cm	130	190	200	210
Height	cm	30+20	40+25	45+30	45+40
Tyre Size	-	185/70	750/16	900/16	900/16
Weight	kg	690	1000	1200	1400
Tipping Angle		42°	42°	42°	42°
Ground Clearance	cm	100	100	100	100

Units	Models			
Capacity	ton	6	8	10
Axle Type	-	Double	Double	Double
Tipping Type	-	rear	rear	rear
Length	cm	450	450	480
Width	cm	200	210	210
Height	cm	60+40	60+50	60+60
Tyre Size	-	900/16	12.5/80	12.5/80
Weight	kg	2500	2700	2900
Tipping Angle		42°	42°	42°
Ground Clearance	cm	110	110	110