



The machine/ the rotating cultivator aside from being used for fluffing the soil and destroying the weeds among the plants such as (beets, beans, sunflowers, corn, soy beans, melon and watermelon etc.) which are planted in a row allows fertilizer to sink in the soil better. Plants develop and grow rapidly due to these processes. Units are in the quality of being adjustable with clips/cuffs that provide the opportunity to work on products planted in different intervals.

The unit is manufactured to be adjustable to the work widths and it has expansion or reduction characteristics with its optional parts.

Depth adjustments are performed by way of 2 tires with mechanical jack located in the front. Easy to assemble fertilizer box and furrow plow can be added optionally.

Specifications	Unit	RC5-75	RC6-45	RC7-45	RC9-45	RC3-70	RC4-70	RC5-70	RC6-70	RC3T-2Y	RC4T-2Y	RC5T-2Y	RC4-35	RC5-35	RC6-35	RC7-35	RC9-35		
Unit Interval(X)	cm		45					70					70					35	
Unit Number	Psc	5	6	7	9	3	4	5	6	5	6	7	4	5	6	7	9		
Blade Number	Cm	10																	
Working Depth	Psc	40	48	56	72	48	64	80	96	64	80	96	32	40	48	56	72		
Working Width (A)	cm	204	249	294	384	180,5	250,5	320,5	390,5	304	374	444	129	164	199	234	304		
Total Width (B)	cm	323	277	327	382	202	277	327	402	327	382	452	147	183	219	255	327		
Length (C)	cm	132																	
Total Height (D)	cm	122																	
Weight	kg	635	720	805	975	615	715	815	915	810	880	1110	530	615	700	765	920		
Min. HP	hp	55-60	65-70	75-80	85-90	55-60	65-70	75-90	85-90	65-70	75-80	85-90	40-50	50-60	60-70	70-80	80-90		